

Docket No. 25216-0849

Patent

UNITED STATES PATENT APPLICATION

FOR

**THREE-DIMENSIONAL CONTACT-SENSITIVE FEATURE FOR ELECTRONIC
DEVICES**

INVENTORS:

SHAWN R. GETTEMY
LAWRENCE LAM
WILLIAM R. HANSON

PREPARED BY:

HICKMAN PALERMO TRUONG & BECKER LLP
1600 WILLOW STREET
SAN JOSE, CALIFORNIA 95125
(408) 414-1080

EXPRESS MAIL CERTIFICATE OF MAILING

"Express Mail" mailing label number EL734779235US

Date of Deposit 5-30-2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Tirena Say

(Typed or printed name of person mailing paper or fee)

Tirena Say
(Signature of person mailing paper or fee)

THREE-DIMENSIONAL CONTACT-SENSITIVE FEATURE FOR ELECTRONIC DEVICES

FIELD OF THE INVENTION

5 The present invention relates to input mechanisms for electronic devices. In particular, the present invention relates to contact-sensitive input features for electronic devices.

BACKGROUND OF THE INVENTION

10 Typical input mechanisms for electronic devices and computers include button mechanisms and mechanical actuation switches. These input mechanisms can be subject to failure through repeated use. They require multiple components that can move relative to one another, and may require hinges, springs or joints that are subject to fatigue.

15 Another type of input mechanism is a digitizer. The digitizer can detect contact on a surface that is typically incorporated with a display. The digitizer may be a component of small computing devices, such as handheld computers, or personal digital assistants (PDAs). An assembly of the digitizer assigns identifying voltage values for different contact points distributed across the digitizer's surface. This allows the user to distinguish a communication by positioning an external object on a specific position of the digitizer.

20 Inputs such as gestures, taps, and drags are made on the surface of the digitizer through contact. Icons or other visual cues may be employed with the digitizer to give a user an indication that contact with a specific position on the digitizer will cause a processor of the device to perform a specific function. Digitizers are relatively planar, so that contact points on the surface of the digitizer are positions on the same plane. When users enter input
25 through a digitizer, the user selects planar positions on the digitizer's surface for contact with the external object.

FIG. 10 is an illustration of a prior art display module 900. The display module 900 is contact-sensitive to produce electrical signals in response to contact. The electrical signals are subsequently converted to input. The display module 900 includes an exterior layer 910, a conductive layer 920, a substrate 930 and a display 940. The exterior layer 910 is a polyester (PET) film. The conductive layer 920 comprises a first conductive film 922, an air gap 926 formed by spacers 945, and a second conductive film 924. The conductive films 922, 924 are formed of Indium Tin Oxide material, which has a paste constituency. The spacers 945 are formed from glass or plastic. The substrate 930 is also formed from glass or plastic. The layers formed above display 940 provide a digitizer for the device. The combination of layers for the digitizer is clear to enable viewing of an image created by display 940.

Mechanical buttons are sometimes preferred for certain functions because they provide a better tactile feedback for the function being requested by the input. For example, navigation buttons for scrolling a display of a handheld computer are often mechanical buttons, because they provide a better feel of movement being created when scrolling the display.

SUMMARY OF THE INVENTION

An electronic device is provided that has a contact-sensitive, three-dimensional surface feature for receiving input. The surface feature enables users to enter input with a tactile feel for a corresponding function. In addition, the surface feature has fewer

5 mechanically combined components, making it more resilient than other input mechanisms.

The user can enter input easier than with more traditional mechanical buttons. Furthermore, embodiments of the invention are operable with fingers as well as a stylus, and may be made to be responsive to grips rather than only distinct touches.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments of the invention are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings. Like reference numerals are intended to refer to similar elements among different figures.

5 FIG. 1 is an exploded, isometric view of an electronic device including a contact-sensitive surface feature, under an embodiment of the invention.

FIG. 2A is a cross-sectional view of a length of the electronic device's housing, cut along lines A-A of FIG. 1, under an embodiment of the invention.

10 FIG. 2B is a cross-sectional view of a length of the electronic device's housing, under another embodiment of the invention.

FIG. 2C is a cross-sectional view of a length of the electronic device's housing, under another embodiment of the invention.

FIG. 3 is a close-up view of a recess shown by line C in FIG. 2A, under an embodiment of the invention.

15 FIG. 4 is a close-up view of another type of surface feature combination for use with an electronic device, under an embodiment of the invention.

FIG. 5 is a close-up view of another type of surface feature combination for use with an electronic device, under an embodiment of the invention.

20 FIG. 6 is a close-up view of another type of surface feature combination for use with an electronic device, under an embodiment of the invention.

FIG. 7 is a cross-sectional view of a length of the electronic device's housing, the housing including a protruding contact-sensitive surface feature, under another embodiment of the invention.

25 FIG. 8 is a cross-sectional view of a length of the electronic device's housing, the housing including a surface mounted feature for entering input, under another embodiment of the invention.

FIG. 9 is a hardware diagram of an electronic device, under an embodiment of the invention.

FIG. 10 is a prior art illustration of a display module including a digitizer.

FIG. 9 is a hardware diagram of an electronic device, under an embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the invention describe three-dimensional contact-sensitive input mechanisms for electronic devices. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, that the present invention may be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring the present invention.

A. Overview

Embodiments of the invention provide an input mechanism for an electronic device. The input mechanism is a shaped feature combined with a contact-sensitive material. The input mechanism may be integrated with a display module or housing of the electronic device.

Under an embodiment of the invention, an electronic device is formed at least partially from a deflectable material that generates an electrical signal in response to contact. The first material is integrated with a portion of the electronic device to provide a shaped feature on an exterior surface of the housing and/or display module. The shaped feature detects contact with an external object on one or more contact points. The contact points correspond to regions where contact is interpreted as a defined input that is signaled for a processor of the electronic device.

In an embodiment, the deflectable material with the shaped feature may be an integrated or unitary function of a display module for the electronic device. Alternatively, the deflectable material and shaped feature can be included with the housing.

In an embodiment, the contact-sensitive feature may be unitarily formed with a housing of the electronic device. The housing of the electronic device may also be combined with a display module. As used herein, unitarily formed means that the components are combined in a manufacturing process to be one component or item for the end user. The components may be combined on a molecular level in order to be unitarily formed.

B. Electronic Device With Contact-Sensitive Surface Feature

FIG. 1 illustrates an electronic device 100 equipped with a display module 120, under an embodiment of the invention. The electronic device 100 includes a housing 110 having a front panel 112 to provide a display surface 122 of housing 110. One or more contact-sensitive, three-dimensional features are formed on an exterior surface of the electronic device 100. The front panel 112 extends between a top 102 and a bottom 104, and between opposing lateral sides 105.

In an embodiment, electronic device 100 is a handheld computer, such as a PDA manufactured by Palm Inc, or a device operating a POCKET PC or WINDOWS CE operating system, manufactured by MICROSOFT. In other embodiments, electronic device 100 includes devices such as touch-sensitive computer tablets, laptop computers, mobile phone devices, or any other device containing processing resources.

In an embodiment, housing 110 is formed at least partially from a contact-sensitive material that generates an electrical signal in response to being contacted by an external object. The material is deflectable or otherwise deformable to generate a voltage differential, causing a current to be generated as a signal.

The display module 120 may include components for detecting contacts on display surface 122. As such, display module 120 may be formed from the same contact-sensitive

material used with housing 110. Alternatively, display module 120 is formed from a different type of contact sensitive material. Still further, housing 110 may contain display module 120, with contact-sensitive features being provided only on display surface 122.

The electronic device 100 includes a plurality of surface features, provided on front panel 112 and/or display surface 122. The surface features are formed from the contact-sensitive material on the remainder of housing 110. The contact-sensitive material is shaped or molded into a three-dimensional feature provided on a surface of housing 110.

In an embodiment, the surface features include a first recess 130 and a pair of second recesses 132. Each recess 130, 132 is formed to detect a contact from an external object, such as a contact mechanism, stylus, finger or other extension. The recesses 130, 132 can be deflected by contact to generate electrical signals that are received as input by electronic device 100.

In one configuration, first recess 130 is positioned adjacent to display surface 122, between the display surface and a bottom edge 104 of housing 110. Second recesses 132 are shown between display surface 122 and a lateral side 105 of housing 110. Each recess 130, 132 is actuatable through contact to signal a command for a processor. The recesses 130, 132 may be pre-associated with one or more functions that can be performed by the processor.

In an embodiment, second recesses 132 are actuatable as switches. That is, the second recesses 132 may be contacted to cause one signal assertion, similar to the operation of a button. The first recess 130 includes multiple contact points to enable users to create multiple signal assertions from the same relative position. The multiple contact points of recess 130 allow for multiple inputs, where each input is distinguished by the position of the external object contacting the first recess 130. For example, recess 130 may be contacted in a portion

proximate to display surface 122 to cause an image appearing on display surface 122 to scroll upwards. Likewise, recess 130 may be contacted in a position distal to display surface 122 to cause an image appearing on display surface 122 to scroll downwards.

FIG. 1 shows that first recess 130 may be coupled to an optional contact mechanism 140 to facilitate entering contacts. The contact mechanism 140 may be coupled to recess 130 during a manufacturing step, or may be configured to be attachable to one or more of the recesses 130, 132 by an end user. In one embodiment, contact mechanism 140 includes a swivel 144 that can be pivoted within first recess 130. The swivel 144 includes an opening 147 for an end piece 148. The end piece 148 fits into opening 147 to provide an exterior contact surface for swivel 144. Swivel 144 includes a bottom portion 145 that rests in recess 130. The bottom portion 145 is contoured or rounded to enable swivel 144 to rock along an axis X and/or Y. In this way, swivel 144 can be pivoted in at least two directions to generate different input signals from recess 130. When pivoted, swivel 144 may be directed into a contact point of recess 130, so as to cause an input signal to be signaled to the processor of electronic device 100.

In another implementation, contact points are provided on recess 130 so that swivel 144 can be directed in eight directions within contact recess 130. Each contact point may correspond to a different input. This allows swivel 144 and end piece 148 to be operated like a multi-directional joystick.

Portions of electronic device 100 are formed from a conductive, contact-sensitive material that is pliable into to different types of surface features. The contact-sensitive material may be integrated with the housing 110 and/or display module 120. A surface feature shaped by the contact-sensitive may be viewed as a portion of display module 120 if

the surface feature is formed as an integrated extension of display 120, even if the surface feature is provided on a region of the electronic device that is outside the footprint of display surface 122. The surface feature may alternatively be viewed as a portion of housing 110 if the surface feature is formed on a structure that is distinct from display module 120.

5 Therefore, the surface feature is formed on a region of a layer formed from the contact-sensitive material. The layer of contact-sensitive may overlap a portion of the front panel's footprint.

FIG. 2A is a cross-sectional view of display module 120 of handheld computer 100, cut along lines A-A of FIG. 1, under an embodiment of the invention. The display module 10 120 includes a digitizer pad 250 to enable the display module to detect contact. An embodiment incorporates a surface feature on a segment of digitizer pad 250. The digitizer pad 250 includes an exterior layer 222, an intermediate conductive section 224, interior layer 226, and substrate 228. The digitizer pad 250 may be incorporated to form a contact-sensitive portion of housing 110, and/or of display module 120. To this end, digitizer pad 250 may be 15 extended over a region that overlaps display module 120 and portions of front panel 112. Opposing sealing elements 229 form a boundary for the conductive portion of digitizer pad 250.

When incorporated with display module 120, digitizer pad 250 extends over a display 230. The display 230 includes pixels or other display elements for creating an image from a 20 processor signal. The layers of display module 120 overlaying display 230 are clear or translucent to enable a user to view the image.

In an embodiment, an exterior layer 222 of the contact-sensitive portion is formed of a PET film. The exterior layer 222 may have a thickness range between 75-180 micrometers.

The exterior layer 222 forms a protective barrier for display module 120, while providing display surface 122 as a smooth area for receiving contact by a stylus tip or other instrument. In an embodiment, segments 117 of front panel 112 are provided over regions of digitizer pad 250 where contact-sensitive input is not wanted, corresponding to where sealing elements 229 are located.

The conductive section 224 includes a first conductive layer 221, an air gap 223 and a second conductive layer 227. The first and second conductive layers 221 and 227 are formed of a material having a property of generating an electrical signal when made to contact one another. A plurality of spacers 225 define air gap 223. The first conductive layer 221 may be deflected into air gap 223 to make contact with second conductive layer 227. When first conductive layer 221 is made to contact second conductive layer 227, a signal is generated for the processor of electronic device 100. The signal may be differentiable to indicate a position where the first conductive layer 221 is made to contact the second conductive layer 227.

In an embodiment, the conductive layers 221 and 227 are each formed by a PET layer combined with a conductive paste. The conductive paste is clear or translucent, and can be formed into a three-dimensional shape during a manufacturing process. At least the first conductive layer 221 is deformable to extend across air gap 223 and make contact with second conductive layer 227, resulting in a voltage signal that is later interpreted as processor signals. Opposing sealing components 229 form a boundary for conductive section 224. The spacers 225 may be formed from glass or clear plastic. In one implementation, the conductive paste for conductive layers 221 and 227 is a clear paste commercially available under the trade name ELECTRODAG, manufactured by ACHESON. This material also has

the property of being pliable for creating shapes and other features. NISSHA of Japan manufactures a film product for conductive layers 221 and 227, using ELECTRODAG.

A thickness of conductive section 224 for each conductive layer 221 and 227 ranges between 150-220 micrometers, and preferably at about 180-200 micrometers. The thickness for air gap 223 may range between 200-400 micrometers, and corresponds to a diameter of spacers 225.

As an alternative, conductive section 224 may be formed of Indium Tin Oxide. The spacer balls 225 may be distributed within conductive section 224 to create a support structure for a three-dimensional feature.

The interior layer 226 is optional. The interior layer 226 may be formed from a PET material similar to exterior layer 222. The conductive section 224 can generate a differentiable voltage signal for substrate 228 when first conductive layer 221 is made to contact second conductive layer 227. The substrate 228 includes traces and other electronic contacts that signal voltage differentials generated from conductive section 224 to a component such as an analog-digital converter. The AD converter converts the voltage differential signal to a digital format for the processor of the electronic device.

In an embodiment, a footprint of display 230 is smaller than a footprint of the other layers of display module 120. As described with FIG. 1, the conductive section 224 of display module 120 may extend across a majority of front panel 112 (FIG. 1).

The surface feature creates a variable thickness in digitizer pad 250. This may correspond to a region of housing 110 and/or display module 120. When the surface feature is employed on front panel 112 (or other housing surface), the front panel 112 may include

impression or shape of variable thickness corresponding to the surface feature. The exterior layer 222 one or more contact points for digitizer 250.

In one embodiment, the layers forming digitizer pad 250 are contoured or shaped with the impression on the exterior surface. FIG. 2A shows that first conductive layer 221, second conductive layer 227, and interior layer 226 may be contoured or indented inward (or outward). The substrate 228 may also be contoured. Therefore, multiple layers of the contact-sensitive portion, including first conductive layer 221 and second conductive layer 227, are contoured to match the shape of recess 130.

FIG. 2B illustrates an embodiment where only the exterior layer 222 and the first conductive layer 221 are contoured to provide recess 130. The second conductive layer 227 is planar with substrate 228. The air gap 223 therefore narrows between the first and second conductive layers 221 and 227. The narrow region of air gap 223 may be used to provide a feature that is more sensitive to contact.

In an embodiment shown by FIGS. 2A and 2B, recess 130 is formed on a portion of display module 120 that extends beyond the footprint of display 230. The recess 130 may be formed to appear as either a portion of housing 110 or as a feature of display module 120.

FIG. 2C illustrates another configuration where recess 130 is formed on a portion of front panel 112 separated from display surface 122 through surface housing segments 117. In this configuration, recess 130 forms a portion of the housing 110 (FIG. 1) for electronic device 100. A rigid layer such as provided by housing segments 117 precludes first conductive layer 221 from being deformed to make contact with second conductive layer 227.

Alternatively, the front panel 112 may include recess 130 and be isotropic with display module 120, so that the front panel and display surface 122 are relatively seamless. The spacers 245 of air gap 223 may be configured to preclude first conductive layer 221 from contacting second conductive layer 227 in that localized region. Thus, the contact required for entering input through the digitizer portion of the housing may be localized to the region of recess 130.

In another embodiment, recess 130 forms a portion of the display surface 122 (FIG. 1) that is inoperative. Still further, another embodiment may provide that recess 130 is formed onto an active portion of display surface 122, within the footprint of display 230.

C. Configurations and Mechanisms For Contact-Sensitive Surface Feature

FIG. 3 is a close-up view of recess 130, under an embodiment of the invention. The recess 130 is shaped to be coupled with contact mechanism 140 (FIG. 1). The exterior layer 222, first conductive layer 221, second conductive layer 227, and interior layer 226 are all contoured to define a shape for recess 130. The substrate 228 (FIGS. 2A and 2B) may also be shaped for recess 130. The first and second conductive layers 221 and 227 are formed from a pliable material that can be shaped to define recess 130, or another feature. One or more contact points may be included on recess 130 to define where first conductive layer 221 may be combined with second conductive layer 227 to signal the processor of the electronic device 100.

According to embodiment, a first contact point 232 is disposed towards bottom 104 of housing 110 (FIG. 1), and a second contact point 234 is disposed towards top 102 of housing 110 (FIG. 1). Each contact point 232, 234 is a region or segment of the shaped feature aligned or otherwise coupled to an electrical lead for detecting a voltage differential

generated in that region from contact. Additional contact points may be similarly provided on recess 130. The swivel 144 of contact mechanism 140 pivots within recess 130 to make contact with contact points 232 and 234. Alternatively, other external objects such as stylus tips and fingers may be used to make contact with contact points 232 and 234.

5 FIG. 4 illustrates another embodiment where a gel cap 330 is positioned within recess 130 to facilitate a user in actuating the contact points 232, 234. The gel cap 330 is fixed to recess 130 at bottom position 335. Adhesives or other fasteners may be used to fix gel cap 330. The mass within gel cap 330 can be moved within recess 130 through contact. When moved, the shape of gel cap 330 can be deformed to apply sufficient pressure for effectuating a contact with contact points 232 and 234. Examples of materials that may be used for gel cap 330 include elastomers and foam.

10 Among advantages provided by gel cap 330, users can more readily use fingers to actuate contact points 232 and 234. The gel cap 330 has a tactile feedback that allows users to make incremental adjustments to the position of the gel cap's mass within recess 130. The gel cap 330 can be gripped with a sustained contact and moved to contact points 232, 234 as desired. Furthermore, the motion required by the user is lateral, to enable contact points 232 and 234 of recess 130 to be actuated when, for example, the user's arm is extended while placing a thumb on the gel cap 330 to enter input.

15 FIG. 5 illustrates a gel filler 420 combined with a moveable surface 430 on recess 130. The gel filler 420 is formed from a sealed gelled mass that is fixed to recess 130 at bottom position 335. The moveable surface 430 is mounted over the gel filler 420. The moveable surface 430 may be fixed to an exterior surface 422 of gel filler 420. The mass of the gel filler 420 may be moved within recess 130 when moveable surface 430 is directed in

one direction or another. The moveable surface 430 is moved to displace the interior mass of gel filler 420, so as to apply pressure or cause contact for actuating contact points 232 and 234.

FIG. 6 illustrates a moveable surface 530 mounted over gel filler 420, under another embodiment of the invention. The moveable surface 530 includes an extension 532 extending from a base 535. The extension 532 facilitates finger contact by a user to displace mass within gel fill 420, so as to enable base 535 to make contact with contact points 232 and 234.

FIG. 7 illustrates another embodiment illustrating a contact-sensitive surface feature shaped as a protrusion 620. The protrusion 620 may include multiple contact points 622, 624. The contact points 622, 624 may be positioned to indicate a function to the user. For example, first contact point 622 may direct the contact towards the display surface 122 (FIG. 1) of electronic device 100 to indicate an upward navigation or scroll for the display surface 122. Likewise, a second contact point 624 may direct away from display surface 122 to indicate navigation or scrolling in an opposite direction.

Shapes other than recesses and protrusions illustrated by FIGS. 1-7 are under different embodiments of the invention. The conductive section 224 may be formed into a variety of shapes to create an input mechanism that facilitates use of electronic device 100.

D. Other Embodiments

While other embodiments described herein provide for a shaped contact-sensitive feature, another embodiment may incorporate three-dimensional contact-sensitive effect on a surface of the housing 110 for the electronic device 100. FIG. 8 is a cross-sectional view illustrating a surface mounted gel volume 730 on display surface 722, formed as an exterior to a first layer 710. The first layer 710 is substantially planar, and forms a portion of a

contact-sensitive display module 720. The gel volume 730 may be fixed to the surface of front panel 112. A moveable component 735 is mounted over the gel volume 730. The moveable component 735 can be directed to displace the interior mass of gel volume 730 so as to cause contact with one or more contact points 722 on the underside of the gel volume 730. For example, the combination of moveable component 735 on gel volume 730 can be operated similar to a button if moveable component 725 is directed towards surface 710.

Alternatively, the combination of the moveable component 735 and gel volume 730 can be operated as a navigation or swivel input mechanism. This may be accomplished by distributing a plurality of contact points on surface 710 in position to be contacted or pressured by movement of moveable component 735.

Structures similar to input mechanisms such as described with recesses 130 and 132 (FIG. 1) may alternatively be employed as sensor mechanisms. In one embodiment, housing 110 (FIG. 1) may be lined with a layer formed from contact-sensitive material, such as ELECTRODAG. At certain regions on housing 110, the contact-sensitive lining may be made to act as sensors that detect contact by a user's hand. The electronic device 100 may be configured based on the sensors detecting the hand or other component. As an example, sensors on a backside of housing 110 may detect whether a user is employing a left hand or right hand to hold the electronic device. The operations of the electronic device 100 may then be configured for left-handed or right-handed users, as detected by the sensors.

E. Hardware Components

FIG. 9 is a block diagram of electronic device 100, including components for receiving input from the contact-sensitive surface or feature shown with FIGS. 1-8.

According to an embodiment, electronic device 100 includes a processor 840 coupled to a

first memory 844 and a second memory 846. The processor 840 is coupled to a display driver 822. The processor 840 combines with display driver 822 to process and signal data for presentation on a module display 820. A digitizer 830 is coupled to processor 840 via an analog-digital (AD) converter 832. The AD converter 832 is coupled to substrate 228 (FIG. 2) to receive voltage differential signals generated through deflection of conductive section 224 (FIG. 2). In an embodiment, AD converter 832 includes first channel 833 and second channel 837 to receive voltage differential signals and generate a corresponding digital signal for processor 840.

The electronic device 100 may include one or more expansion slots. In an embodiment shown, a first peripheral port 802 enables one or more types of accessory devices to be connected to processor 840. In addition, electronic device 100 may include a wireless peripheral port 804 that enables information to be communicated to processor 840 from an external source. The wireless peripheral port 804 forwards incoming communications to an amplifier 806 for processor 840. A second processor 808 intercepts communications incoming to and/or outgoing from wireless peripheral port 804 for purpose of facilitating conversion of data signals between formats and protocols of wireless communications, and those that can be processed by processor 840.

The display module 820 cooperates with display driver 822 to display images on display surface 822. The first memory 844 may be non-volatile. The processor 840 combines with display driver 822 to present the data in a paginated format on display module 820.

F. Conclusion

In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and

changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
223